

# SonicWall TZ series

Integrated threat prevention and SD-Branch platform for small/medium organizations and distributed enterprises

The SonicWall TZ series enables small to mid-size organizations and distributed enterprises realize the benefits of an integrated security solution that checks all the boxes. Combining high-speed threat prevention and software-defined wide area networking (SD-WAN) technology with an extensive range of networking and wireless features plus simplified deployment and centralized management, the TZ series provides a unified security solution at a low total cost of ownership.

## Flexible, integrated security solution

The foundation of the TZ series is SonicOS, SonicWall's feature-rich operating system. Firewalls supporting the latest SonicOS 7.0 OS, features new modern-look UI/UX, advanced security, networking and simplified policy management capabilities.

SonicOS further includes a powerful set of capabilities that provides organizations with the flexibility to tune these Unified Threat Management (UTM) firewalls to their specific network requirements. For example, creating a secure high-speed wireless network is simplified through a built-in wireless controller which supports IEEE 802.11 standards or by adding our SonicWave 802.11ac Wave 2 access points. To reduce the cost and complexity of connecting high-speed wireless access points and other Power over Ethernet (PoE)-enabled devices such as IP cameras, phones and printers, the TZ300P, TZ600P and TZ570P provide PoE/PoE+ power.

Distributed retail businesses and campus environments can take advantage of the many tools in SonicOS to gain even greater benefits. Branch locations are able to exchange information securely with the central office using virtual private networking (VPN). Creating virtual LANs (VLANs) enables segmentation of the network into separate corporate and customer groups with rules that determine the level of communication with devices on other VLANs. SD-WAN offers a secure alternative to costly MPLS circuits while delivering consistent application performance and availability. Deploying TZ firewalls to remote locations is easy using Zero-Touch Deployment which enables provisioning of the firewall remotely through the cloud.

## Superior threat prevention and performance

Our vision for securing networks in today's continually-evolving cyber threat landscape is automated, real-time threat detection and prevention. Through a combination of cloud-based and on-box technologies we deliver protection to our firewalls that's been validated by independent third-party testing for its extremely high security effectiveness. Unknown threats are sent to SonicWall's cloud-based Capture Advanced Threat Protection (ATP) multi-engine sandbox for analysis. Enhancing Capture ATP is our patent-pending Real-Time Deep Memory Inspection (RTDMI™) technology. The RTDMI engine detects and blocks malware



## Benefits:

### Flexible, integrated security solution

- Multi-gigabit interfaces in a desktop form factor
- Secure SD-Branch with SD-WAN
- Powerful SonicOS 7.0 operating system
- High-speed 802.11ac Wave 2 wireless
- Power over Ethernet (PoE/PoE+)
- 5G/4G/LTE support
- Built-in and expandable storage
- Redundant power

### Superior threat prevention and performance

- Patent-pending real-time deep memory inspection technology
- Patented reassembly-free deep packet inspection technology
- TLS 1.3 support
- Industry-validated security effectiveness

### Easy deployment, setup and ongoing management

- Zero-Touch Deployment
- Cloud-based and on-premises centralized management
- SonicExpress App onboarding

and zero-day threats by inspecting directly in memory. RTDMI technology is precise, minimizes false positives, and identifies and mitigates sophisticated attacks where the malware's weaponry is exposed for less than 100 nanoseconds. In combination, our patented single-pass Reassembly-Free Deep Packet Inspection (RFDPI) engine examines every byte of every packet, inspecting both inbound and outbound traffic directly on the firewall. By leveraging Capture ATP with RTDMI technology in the SonicWall Capture Cloud Platform in addition to on-box capabilities including intrusion prevention, anti-malware and web/URL filtering, TZ series firewalls stop malware, ransomware and other threats at the gateway. For mobile devices used outside the firewall perimeter, SonicWall Capture Client provides an added layer of protection by applying advanced threat protection techniques such as machine learning and system rollback. Capture Client also leverages the deep inspection of encrypted TLS traffic (DPI-SSL) on TZ series firewalls by installing and managing trusted TLS certificates.

The continued growth in the use of encryption to secure web sessions means it is imperative firewalls are able

to scan encrypted traffic for threats. TZ series firewalls provide complete protection by performing full decryption and inspection of TLS/SSL and SSH encrypted connections regardless of port or protocol. The firewall searches for protocol non-compliance, threats, zero-days, intrusions, and even defined criteria by looking deep inside every packet. The deep packet inspection engine detects and prevents hidden attacks that leverage cryptography. It also blocks encrypted malware downloads, ceases the spread of infections and thwarts command and control (C&C) communications and data exfiltration. Inclusion and exclusion rules allow total control to customize which traffic is subjected to decryption and inspection based on specific organizational compliance and/or legal requirements.

TZ670 and TZ570 provides TLS 1.3 support, which offers several changes that improves performance and security, while eliminating complexities.


### Easy deployment, setup and ongoing management

SonicWall makes it easy to configure and manage TZ series firewalls and SonicWave 802.11ac Wave 2 access

points no matter where you deploy them. Centralized management, reporting, licensing and analytics are handled through our cloud-based Capture Security Center which offers the ultimate in visibility, agility and capacity to centrally govern the entire SonicWall security ecosystem from a single pane of glass.

A key component of the Capture Security Center is Zero-Touch Deployment. This cloud-based feature simplifies and speeds the deployment and provisioning of SonicWall firewalls at remote and branch office locations. The process requires minimal user intervention, and is fully automated to operationalize firewalls at scale in just a few steps. This significantly reduces the time, cost and complexity associated with installation and configuration, while security and connectivity occurs instantly and automatically. Together, the simplified deployment and setup along with the ease of management enable organizations to lower their total cost of ownership and realize a high return on investment.

\* 802.11ac currently not available on SOHO/SOHO 250 models; SOHO/SOHO 250 models support 802.11a/b/g/n



### Integrated Security and Power for Your PoE-enabled Devices

Provide power to your PoE-enabled devices without the cost and complexity of a Power over Ethernet switch or injector. TZ300P, TZ600P and TZ570P firewalls integrate IEEE 802.3at technology to power PoE and PoE+ devices such as wireless access points, cameras, IP phones and more. The firewall scans all traffic coming from and going to each device using deep packet inspection technology and then removes harmful threats such as malware and intrusions, even over encrypted connections.


## Capture Cloud Platform

SonicWall's Capture Cloud Platform delivers cloud-based threat prevention and network management plus reporting and analytics for organizations of any size. The platform consolidates threat intelligence gathered from multiple sources including our award-winning multi-engine network sandboxing service, Capture Advanced Threat Protection, as well as more than 1 million SonicWall sensors located around the globe.

If data coming into the network is found to contain previously-unseen malicious code, SonicWall's dedicated, in-house Capture Labs threat research team develops signatures that are stored in the Capture Cloud Platform database and deployed to customer firewalls for up-to-date protection. New updates take effect immediately without reboots or interruptions. The signatures resident on the appliance protect against wide

classes of attacks, covering tens of thousands of individual threats. In addition to the countermeasures on the appliance, TZ firewalls also have continuous access to the Capture Cloud Platform database which extends the onboard signature intelligence with tens of millions of signatures.

In addition to providing threat prevention, the Capture Cloud Platform offers single pane of glass management and administrators can easily create both real-time and historical reports on network activity.



## Advanced threat protection

At the center of SonicWall's automated, real-time breach prevention are two advanced malware detection technologies; Capture Advanced Threat Protection™ (Capture ATP) and Capture Security appliance™ (CSa).


Capture ATP is a cloud-based multi-engine sandbox platform, which includes Real-Time Deep Memory Inspection™ (RTDMI), virtualized sandboxing, full system emulation and hypervisor level analysis technology. CSa is an on-premises device that features RTDMI, which utilizes memory-based static and dynamic techniques for fast and accurate verdicts. Both solutions extend advanced threat protection to detect and prevent zero-day threats in a variety of SonicWall solutions such as next-generation firewalls.

Suspicious files are sent to either solution where they are analyzed using deep learning algorithms with the option to hold them at the gateway until a verdict is determined. In the case of Capture ATP, when files are identified

as malicious, they are blocked, and a hash is immediately created within the Capture ATP database for all customers to leverage to block follow-on attacks. These signatures are eventually sent to firewalls to create static defenses. Results generated by CSa are not shared outside your organization for privacy and compliance reasons.

These services analyze a broad range of operating systems and file types, including executable programs, DLL, PDFs, MS Office documents, archives, JAR and APK.

For complete endpoint protection, the SonicWall Capture Client combines next-generation antivirus technology with SonicWall's cloud-based multi-engine sandbox with optional integration with SonicWall firewalls.



## Reassembly-Free Deep Packet Inspection engine



The SonicWall Reassembly-Free Deep Packet Inspection (RFDPI) is a single-pass, low latency inspection system that performs stream-based, bi-directional traffic analysis at high speed without proxying or buffering to effectively uncover intrusion attempts and malware downloads while identifying application traffic regardless of port and protocol. This proprietary engine relies on streaming traffic payload inspection to detect threats at Layers 3-7, and takes

network streams through extensive and repeated normalization and decryption in order to neutralize advanced evasion techniques that seek to confuse detection engines and sneak malicious code into the network.

Once a packet undergoes the necessary pre-processing, including TLS/SSL decryption, it is analyzed against a single, proprietary memory representation of three signature databases: intrusion attacks, malware and applications. The connection state is then advanced to represent the position of the stream

relative to these databases until it encounters a state of attack, or other “match” event, at which point a pre-set action is taken.

In most cases, the connection is terminated and proper logging and notification events are created. However, the engine can also be configured for inspection only or, in case of application detection, to provide Layer 7 bandwidth management services for the remainder of the application stream as soon as the application is identified.



## Centralized management and reporting

For highly regulated organizations wanting to achieve a fully coordinated security governance, compliance and risk management strategy, SonicWall provides administrators a unified, secure and extensible platform to manage SonicWall firewalls, wireless


access points and Dell N-Series and X-Series switches through a correlated and auditable workflow process. Enterprises can easily consolidate the management of security appliances, reduce administrative and troubleshooting complexities, and govern all operational aspects of the security infrastructure, including centralized policy management and enforcement; real-time event monitoring; user activities; application identifications; flow analytics and forensics; compliance and audit reporting; and more. In addition, enterprises meet the firewall’s change management requirements through workflow automation which provides the

agility and confidence to deploy the right firewall policies at the right time and in conformance with compliance regulations. Available on premises as SonicWall Global Management System and in the cloud as Capture Security Center, SonicWall management and reporting solutions provide a coherent way to manage network security by business processes and service levels, dramatically simplifying lifecycle management of your overall security environments compared to managing on a device-by-device basis.

## Distributed networks

Because of their flexibility, TZ series firewalls are ideally suited for both distributed enterprise and single site deployments. In distributed networks like those found in retail organizations, each site has its own TZ firewall which connects to the Internet often through a local provider using a DSL, cable or 3G/4G connection. In addition to Internet access, each firewall utilizes an Ethernet connection to transport packets between remote sites and the central headquarters. Web services and SaaS applications such as Office 365, Salesforce and others are served up from the data center. Through mesh VPN technology, IT administrators can create a hub and spoke configuration for the safe transport of data between all locations.

The SD-WAN technology in SonicOS is a perfect complement to TZ firewalls deployed at remote and branch sites.




Instead of relying on more expensive legacy technologies such as MPLS and T1, organizations using SD-WAN can choose lower-cost public Internet

services while continuing to achieve a high level of application availability and predictable performance.

## Capture Security Center

Tying the distributed network together is SonicWall's cloud-based Capture Security Center (CSC) which centralizes deployment, ongoing management and real-time analytics of the TZ firewalls. A key feature of CSC is Zero-Touch Deployment. Configuring and deploying firewalls across multiple sites is time-consuming and requires on-site personnel. However Zero-Touch Deployment removes these challenges by simplifying and speeding the deployment and provisioning of SonicWall firewalls remotely through the cloud. Similarly, CSC eases ongoing management by providing cloud-based single-pane-of-glass management for SonicWall devices on the network. For complete situational awareness of the network security environment, SonicWall Analytics offers a single-pane view into all activity occurring inside the network. Organizations gain a deeper understanding of application usage and performance while reducing the possibility of Shadow IT.




Part of CSC, SonicWall Network Security Manager (NSM), a multi-tenant centralized firewall manager, allows you to centrally manage all firewall operations error-free by adhering to auditable workflows. Its native analytic engine gives single-pane visibility and lets you monitor and uncover threats

by unifying and correlating logs across all firewalls. NSM also helps you stay compliant as it provides full audit trail of every configuration changes and granular reporting. NSM scales to any size organization managing networks with up to thousands of firewall devices deployed across many locations.


### SonicWall TZ670 series

Designed for mid-sized organizations and distributed enterprise with SD-Branch locations, the TZ670 delivers industry-validated security effectiveness with best-in-class price-performance.




### SonicWall TZ570 series

Designed for small to mid-sized organizations and distributed enterprise with SD-Branch locations, the TZ570 series deliver industry-validated security effectiveness with best-in-class price-performance.




### SonicWall TZ600 series

For emerging enterprises, retail and branch offices looking for security, performance and options such as 802.3at PoE+ support at a value price, the SonicWall TZ600 secures networks with enterprise-class features and uncompromising performance.




### SonicWall TZ500 series

For growing branch offices and SMBs, the SonicWall TZ500 series delivers highly effective, no-compromise protection with network productivity and optional integrated 802.11ac dual-band wireless.



### SonicWall TZ400 series

For small business, retail and branch office locations, the SonicWall TZ400 series delivers enterprise-grade protection. Flexible wireless deployment is available with optional 802.11ac dual-band wireless integrated into the firewall.




### SonicWall TZ350/TZ300 series

The SonicWall TZ300 and TZ350 series offer an all-in-one solution that protects networks from advanced attacks. Unlike consumer grade products, these UTM firewalls combine high-speed intrusion prevention, anti-malware and content/URL filtering plus broad secure mobile access support for laptops, smartphones and tablets along with optional integrated 802.11ac wireless. In addition, the TZ300 offers optional 802.3at PoE+ to power PoE-enabled devices.



### SonicWall SOHO 250/SOHO series

For wired and wireless small and home office environments, the SonicWall SOHO 250 and SOHO series deliver the same business-class protection large organizations require at a more affordable price point. Add optional 802.11n wireless to provide employees, customers and guests with secure wireless connectivity.



#### Partner Enabled Services

Need help to plan, deploy or optimize your SonicWall solution? SonicWall Advanced Services Partners are trained to provide you with world class professional services. Learn more at [www.sonicwall.com/PES](http://www.sonicwall.com/PES).



## SonicOS 7.0 feature summary

### Firewall

- Stateful packet inspection
- Reassembly-Free Deep Packet Inspection
- DDoS attack protection (UDP/ICMP/SYN flood)
- IPv4/IPv6 support
- Biometric authentication for remote access
- DNS proxy
- Full API support
- SonicWall Switch integration
- SD-WAN scalability
- SD-WAN Usability Wizard<sup>1</sup>
- SonicCoreX and SonicOS containerization<sup>1</sup>
- Connections scalability (SPI, DPI, DPI SSL)

### Enhanced dashboard<sup>1</sup>

- Enhanced device view
- Top traffic and user summary
- Insights to threats
- Notification center

### TLS/SSL/SSH decryption and inspection

- TLS 1.3 with enhanced security<sup>1</sup>
- Deep packet inspection for TLS/SSL/SSH
- Inclusion/exclusion of objects, groups or hostnames
- SSL control
- Enhancements for DPI-SSL with CFS
- Granular DPI SSL controls per zone or rule

### Capture advanced threat protection<sup>2</sup>

- Real-Time Deep Memory Inspection
- Cloud-based multi-engine analysis
- Virtualized sandboxing
- Hypervisor level analysis
- Full system emulation
- Broad file type examination
- Automated and manual submission
- Real-time threat intelligence updates
- Block until verdict
- Capture Client

### Intrusion prevention<sup>2</sup>

- Signature-based scanning
- Automatic signature updates
- Bi-directional inspection
- Granular IPS rule capability
- GeolP enforcement
- Botnet filtering with dynamic list
- Regular expression matching

### Anti-malware<sup>2</sup>

- Stream-based malware scanning
- Gateway anti-virus
- Gateway anti-spyware
- Bi-directional inspection
- No file size limitation
- Cloud malware database

### Application identification<sup>2</sup>

- Application control
- Application bandwidth management
- Custom application signature creation
- Data leakage prevention

- Application reporting over NetFlow/IPFIX
- Comprehensive application signature database

### Traffic visualization and analytics

- User activity
- Application/bandwidth/threat usage
- Cloud-based analytics

### HTTP/HTTPS Web content filtering<sup>2</sup>

- URL filtering
- Proxy avoidance
- Keyword blocking
- Policy-based filtering (exclusion/inclusion)
- HTTP header insertion
- Bandwidth manage CFS rating categories
- Unified policy model with app control
- Content Filtering Client

### VPN

- Secure SD-WAN
- Auto-provision VPN
- IPSec VPN for site-to-site connectivity
- SSL VPN and IPSec client remote access
- Redundant VPN gateway
- Mobile Connect for iOS, Mac OS X, Windows, Chrome, Android and Kindle Fire
- Route-based VPN (OSPF, RIP, BGP)

### Networking

- PortShield
- Jumbo frames
- Path MTU discovery
- Enhanced logging
- VLAN trunking
- Port mirroring (NSa 2650 and above)
- Layer-2 QoS
- Port security
- Dynamic routing (RIP/OSPF/BGP)
- SonicWall wireless controller
- Policy-based routing (ToS/metric and ECMP)
- NAT
- DHCP server
- Bandwidth management
- A/P high availability with state sync
- Inbound/outbound load balancing
- High availability - Active/Standby with state sync
- L2 bridge, wire/virtual wire mode, tap mode, NAT mode
- Asymmetric routing
- Common Access Card (CAC) support

### VoIP

- Granular QoS control
- Bandwidth management
- DPI for VoIP traffic
- H.323 gatekeeper and SIP proxy support

### Management, monitoring and support

- Capture Security Appliance (CSa) support
- Capture Threat Assessment (CTA) v2.0
  - New design or template
  - Industry and global average comparison
- New UI/UX, Intuitive feature layout<sup>1</sup>

- Dashboard
- Device information, application, threats
- Topology view
- Simplified policy creation and management
- Policy/Objects usage statistics<sup>1</sup>
  - Used vs Un-used
  - Active vs Inactive
- Global search for static data
- Storage support<sup>1</sup>
- Internal and external storage management<sup>1</sup>
- WWAN USB card support (5G/LTE/4G/3G)
- Network Security Manager (NSM) support
- Web GUI
- Command line interface (CLI)
- Zero-Touch registration & provisioning
- CSC Simple Reporting<sup>1</sup>
- SonicExpress mobile app support
- SNMPv2/v3
- Centralized management and reporting with SonicWall Global Management System (GMS)<sup>2</sup>
- Logging
- Netflow/IPFix exporting
- Cloud-based configuration backup
- BlueCoat security analytics platform
- Application and bandwidth visualization
- IPv4 and IPv6 management
- CD management screen
- Dell N-Series and X-Series switch management including cascaded switches

### Debugging and diagnostics

- Enhanced packet monitoring
- SSH terminal on UI

### Wireless

- SonicWave AP cloud management
- WIDS/WIPS
- Rogue AP prevention
- Fast roaming (802.11k/r/v)
- 802.11s mesh networking
- Auto-channel selection
- RF spectrum analysis
- Floor plan view
- Topology view
- Band steering
- Beamforming
- AirTime fairness
- Bluetooth Low Energy
- MiFi extender
- RF enhancements and improvements
- Guest cyclic quota

### Integrated Wireless Models

- 802.11ac Wave 2 wireless (TZ570W)
- Dual-band (2.4 GHz and 5.0 GHz)
- 802.11 a/b/g/n/ac wireless standards
- Wireless intrusion detection and prevention
- Wireless guest services
- Lightweight hotspot messaging
- Virtual access point segmentation
- Captive portal
- Cloud ACL

<sup>1</sup> New feature, available on SonicOS 7.0

<sup>2</sup> Requires added subscription

## SonicWall TZ Series system specifications – SOHO, SOHO 250, TZ300 and TZ350

| FIREWALL GENERAL  | SOHO SERIES  | SOHO 250 SERIES  | TZ300 SERIES                       | TZ350 SERIES             |
|---|--|------------------|------------------------------------|--------------------------|
| Operating system  | SonicOS  |                  |                                    |                          |
| Interfaces  | 5x1GbE, 1 USB, 1 Console   |                  | 5x1GbE, 1 USB, 1 Console           | 5x1GbE, 1 USB, 1 Console |
| Power over Ethernet (PoE) support                                   | —  | —                | TZ300P - 2 ports (2 PoE or 1 PoE+) | —                        |
| Expansion   | USB  |                  |                                    |                          |
| Management  | CLI, SSH, Web UI, Capture Security Center, GMS, REST APIs  |                  |                                    |                          |
| Single Sign-On (SSO) Users  | 250  | 350              | 500                                | 500                      |
| VLAN interfaces   | 25   |                  |                                    |                          |
| Access points supported (maximum)                                   | 2  | 4                | 8                                  | 8                        |
| FIREWALL/VPN PERFORMANCE  | SOHO SERIES  | SOHO 250 SERIES  | TZ300 SERIES                       | TZ350 SERIES             |
| Firewall inspection throughput <sup>1</sup>                         | 300 Mbps   | 600 Mbps         | 750 Mbps                           | 1.0 Gbps                 |
| Threat Prevention throughput <sup>2</sup>                           | 150 Mbps   | 200 Mbps         | 235 Mbps                           | 335 Mbps                 |
| Application inspection throughput <sup>2</sup>                      | —  | 275 Mbps         | 375 Mbps                           | 600 Mbps                 |
| IPS throughput <sup>2</sup>   | 200 Mbps   | 250 Mbps         | 300 Mbps                           | 400 Mbps                 |
| Anti-malware inspection throughput <sup>2</sup>                     | 150 Mbps   | 200 Mbps         | 235 Mbps                           | 335 Mbps                 |
| TLS/SSL inspection and decryption throughput (DPI SSL) <sup>2</sup> | 30 Mbps  | 50 Mbps          | 60 Mbps                            | 65 Mbps                  |
| IPSec VPN throughput <sup>3</sup>                                   | 150 Mbps   | 200 Mbps         | 300 Mbps                           | 430 Mbps                 |
| Connections per second  | 1,800  | 3,000            | 5,000                              | 6,000                    |
| Maximum connections (SPI)   | 10,000   | 50,000           | 100,000                            | 100,000                  |
| Maximum connections (DPI)   | 10,000   | 50,000           | 90,000                             | 90,000                   |
| Maximum connections (DPI SSL)                                       | 250  | 25,000           | 25,000                             | 25,000                   |
| VPN   | SOHO SERIES  | SOHO 250 SERIES  | TZ300 SERIES                       | TZ350 SERIES             |
| Site-to-site VPN tunnels  | 10   | 10               | 10                                 | 15                       |
| IPSec VPN clients (maximum)   | 1 (5)  | 1 (5)            | 1 (10)                             | 2 (10)                   |
| SSL VPN licenses (maximum)  | 1 (10)   | 1 (25)           | 1 (50)                             | 1 (75)                   |
| Virtual assist bundled (maximum)                                    | —  | 1 (30-day trial) | 1 (30-day trial)                   | 1 (30-day trial)         |
| Encryption/authentication   | DES, 3DES, AES (128, 192, 256-bit), MD5, SHA-1, Suite B Cryptography   |                  |                                    |                          |
| Key exchange  | Diffie Hellman Groups 1, 2, 5, 14v   |                  |                                    |                          |
| Route-based VPN   | RIP, OSPF, BGP <sup>4</sup>  |                  |                                    |                          |
| VPN features  | Dead Peer Detection, DHCP Over VPN, IPSec NAT Traversal, Redundant VPN Gateway, Route-based VPN  |                  |                                    |                          |
| Global VPN client platforms supported                               | Microsoft® Windows Vista 32/64-bit, Windows 7 32/64-bit, Windows 8.0 32/64-bit, Windows 8.1 32/64-bit, Windows 10  |                  |                                    |                          |
| NetExtender   | Microsoft Windows Vista 32/64-bit, Windows 7, Windows 8.0 32/64-bit, Windows 8.1 32/64-bit, Mac OS X 10.4+, Linux FC3+/Ubuntu 7+/OpenSUSE                    |                  |                                    |                          |
| Mobile Connect  | Apple® iOS, Mac OS X, Google® Android™, Kindle Fire, Chrome, Windows 8.1 (Embedded)  |                  |                                    |                          |
| SECURITY SERVICES   | SOHO SERIES  | SOHO 250 SERIES  | TZ300 SERIES                       | TZ350 SERIES             |
| Deep Packet Inspection services                                     | Gateway Anti-Virus, Anti-Spyware, Intrusion Prevention, DPI SSL  |                  |                                    |                          |
| Content Filtering Service (CFS)                                     | HTTP URL, HTTPS IP, keyword and content scanning, Comprehensive filtering based on file types such as ActiveX, Java, Cookies for privacy, allow/forbid lists |                  |                                    |                          |
| Comprehensive Anti-Spam Service                                     | Supported  |                  |                                    |                          |
| Application Visualization   | No   | Yes              | Yes                                | Yes                      |
| Application Control   | Yes  | Yes              | Yes                                | Yes                      |
| Capture Advanced Threat Protection                                  | No   | Yes              | Yes                                | Yes                      |
| NETWORKING  | SOHO SERIES  | SOHO 250 SERIES  | TZ300 SERIES                       | TZ350 SERIES             |
| IP address assignment   | Static, (DHCP, PPPoE, L2TP and PPTP client), Internal DHCP server, DHCP relay  |                  |                                    |                          |
| NAT modes   | 1:1, 1:many, many:1, many:many, flexible NAT (overlapping IPs), PAT, transparent mode  |                  |                                    |                          |
| Routing protocols <sup>4</sup>                                      | BGP <sup>4</sup> , OSPF, RIPv1/v2, static routes, policy-based routing   |                  |                                    |                          |
| QoS   | Bandwidth priority, max bandwidth, guaranteed bandwidth, DSCP marking, 802.1e (WMM)  |                  |                                    |                          |

SonicWall TZ series specifications cont'd – SOHO, SOHO 250, TZ300 and TZ350

| NETWORKING CONT'D                             | SOHO SERIES  | SOHO 250 SERIES | TZ300 SERIES  | TZ350 SERIES                                |
|---|--|-----------------|---|---|
| Authentication                                | LDAP (multiple domains), XAUTH/RADIUS, SSO, Novell, internal user database   |                 | LDAP (multiple domains), XAUTH/RADIUS, SSO, Novell, internal user database, Terminal Services, Citrix, Common Access Card (CAC)             |   |
| Local user database                           |  |                 | 150   |   |
| VoIP  | Full H.323v1-5, SIP  |                 |   |   |
| Standards                                     | TCP/IP, UDP, ICMP, HTTP, HTTPS, IPSec, ISAKMP/IKE, SNMP, DHCP, PPPoE, L2TP, PPTP, RADIUS, IEEE 802.3                                       |                 |   |   |
| Certifications <sup>5</sup>                   | FIPS 140-2 (with Suite B) Level 2, UC APL, IPv6 (Phase 2), ICSA Network Firewall, ICSA Anti-virus, Common Criteria NDPP (Firewall and IPS) |                 |   |   |
| Common Access Card (CAC)                      | Supported  |                 |   |   |
| High availability                             | No   |                 | Active/standby  |   |
| HARDWARE                                      | SOHO SERIES  | SOHO 250 SERIES | TZ300 SERIES  | TZ350 SERIES                                |
| Form factor                                   | Desktop  |                 |   |   |
| Power supply                                  | 24W external   |                 | 24W external<br>65W external<br>(TZ300P only)   | 24W external                                |
| Maximum power consumption (W)                 | 6.4 / 11.3   | 6.9 / 11.3      | 6.9 / 12.0  | 6.9 / 12.0                                  |
| Input power                                   | 100 to 240 VAC, 50-60 Hz, 1 A  |                 |   |   |
| Total heat dissipation                        | 21.8 / 38.7 BTU  | 23.5 / 38.7 BTU | 23.5 / 40.9 BTU   | 23.5 / 40.9 BTU                             |
| Dimensions                                    | 3.6 x 14.1 x 19 cm<br>1.42 x 5.55 x 7.48 in  |                 | 3.5 x 13.4 x 19 cm<br>1.38 x 5.28 x 7.48 in   | 3.5 x 13.4 x 19 cm<br>1.38 x 5.28 x 7.48 in |
| Weight  | 0.34 kg / 0.75 lbs<br>0.48 kg / 1.06 lbs   |                 | 0.73 kg / 1.61 lbs<br>0.84 kg / 1.85 lbs  | 0.73 kg / 1.61 lbs<br>0.84 kg / 1.85 lbs    |
| WEEE weight                                   | 0.80 kg / 1.76 lbs<br>0.94 kg / 2.07 lbs   |                 | 1.15 kg / 2.53 lbs<br>1.26 kg / 2.78 lbs  | 1.15 kg / 2.53 lbs<br>1.26 kg / 2.78 lbs    |
| Shipping weight                               | 1.20 kg / 2.64 lbs<br>1.34 kg / 2.95 lbs   |                 | 1.37 kg / 3.02 lbs<br>1.48 kg / 3.26 lbs  | 1.37 kg / 3.02 lbs<br>1.48 kg / 3.26 lbs    |
| MTBF (in years)                               | 58.9/56.1 (wireless)   | 56.1            | 56.1  | 56.1  |
| Environment (Operating/Storage)               | 32°-105° F (0°-40° C)/-40° to 158° F (-40° to 70° C)   |                 |   |   |
| Humidity                                      | 5-95% non-condensing   |                 |   |   |
| REGULATORY                                    | SOHO SERIES  | SOHO 250 SERIES | TZ300 SERIES  | TZ350 SERIES                                |
| Major regulatory compliance (wired models)    | FCC Class B, ICES Class B, CE (EMC, LVD, RoHS), C-Tick, VCCI Class B, UL, cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH, KCC/MSIP, ANATEL |                 | FCC Class B, ICES Class B, CE (EMC, LVD, RoHS), C-Tick, VCCI Class B, UL, cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH, KCC/MSIP, ANATEL  |   |
| Major regulatory compliance (wireless models) | FCC Class B, FCC RF ICES Class B, IC RF CE (RED, RoHS), RCM, VCCI Class B, MIC/TELEC, UL, cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH   |                 | FCC Class B, FCC RF ICES Class B, IC RF CE (RED, RoHS), RCM, VCCI Class B, MIC/TELEC, UL, cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH    |   |
| INTEGRATED WIRELESS                           | SOHO SERIES  | SOHO 250 SERIES | TZ300 SERIES  | TZ350 SERIES                                |
| Standards                                     | 802.11 a/b/g/n   |                 | 802.11a/b/g/n/ac (WEP, WPA, WPA2, 802.11i, TKIP, PSK, 02.1x, EAP-PEAP, EAP-TTLS)  |   |
| Frequency bands <sup>6</sup>                  | 802.11a: 5.180-5.825 GHz; 802.11b/g: 2.412-2.472 GHz; 802.11n: 2.412-2.472 GHz, 5.180-5.825 GHz  |                 | 802.11a: 5.180-5.825 GHz; 802.11b/g: 2.412-2.472 GHz; 802.11n: 2.412-2.472 GHz, 5.180-5.825 GHz; 802.11ac: 2.412-2.472 GHz, 5.180-5.825 GHz |   |

SonicWall TZ series system specifications cont'd – SOHO, SOHO 250, TZ300 and TZ350

| INTEGRATED WIRELESS            | SOHO SERIES   | SOHO 250 SERIES | TZ300 SERIES   | TZ350 SERIES |
|--------------------------------|---|-----------------|--|--------------|
| Operating Channels             | 802.11a: US and Canada 12, Europe 11, Japan 4, Singapore 4, Taiwan 4; 802.11b/g: US and Canada 1-11, Europe 1-13, Japan 1-14 (14-802.11b only); 802.11n (2.4 GHz): US and Canada 1-11, Europe 1-13, Japan 1-13; 802.11n (5 GHz): US and Canada 36-48/149-165, Europe 36-48, Japan 36-48, Spain 36-48/52-64; |                 | 802.11a: US and Canada 12, Europe 11, Japan 4, Singapore 4, Taiwan 4; 802.11b/g: US and Canada 1-11, Europe 1-13, Japan 1-14 (14-802.11b only); 802.11n (2.4 GHz): US and Canada 1-11, Europe 1-13, Japan 1-13; 802.11n (5 GHz): US and Canada 36-48/149-165, Europe 36-48, Japan 36-48, Spain 36-48/52-64; 802.11ac: US and Canada 36-48/149-165, Europe 36-48, Japan 36-48, Spain 36-48/52-64  |              |
| Transmit output power          | Based on the regulatory domain specified by the system administrator  |                 |  |              |
| Transmit power control         | Supported   |                 |  |              |
| Data rates supported           | 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps per channel; 802.11b: 1, 2, 5.5, 11 Mbps per channel; 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps per channel; 802.11n: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2, 15, 30, 45, 60, 90, 120, 135, 150 Mbps per channel   |                 | 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps per channel; 802.11b: 1, 2, 5.5, 11 Mbps per channel; 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps per channel; 802.11n: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2, 15, 30, 45, 60, 90, 120, 135, 150 Mbps per channel; 802.11ac: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2, 86.7, 96.3, 15, 30, 45, 60, 90, 120, 135, 150, 180, 200, 32.5, 65, 97.5, 130, 195, 260, 292.5, 325, 390, 433.3, 65, 130, 195, 260, 390, 520, 585, 650, 780, 866.7 Mbps per channel |              |
| Modulation technology spectrum | 802.11a: Orthogonal Frequency Division Multiplexing (OFDM); 802.11b: Direct Sequence Spread Spectrum (DSSS); 802.11g: Orthogonal Frequency Division Multiplexing (OFDM)/Direct Sequence Spread Spectrum (DSSS); 802.11n: Orthogonal Frequency Division Multiplexing (OFDM)                                  |                 | 802.11a: Orthogonal Frequency Division Multiplexing (OFDM); 802.11b: Direct Sequence Spread Spectrum (DSSS); 802.11g: Orthogonal Frequency Division Multiplexing (OFDM)/Direct Sequence Spread Spectrum (DSSS); 802.11n: Orthogonal Frequency Division Multiplexing (OFDM); 802.11ac: Orthogonal Frequency Division Multiplexing (OFDM)  |              |

\*Future use

<sup>1</sup> Testing Methodologies: Maximum performance based on RFC 2544 (for firewall). Actual performance may vary depending on network conditions and activated services.

<sup>2</sup> Threat Prevention/GatewayAV/Anti-Spyware/IPS throughput measured using industry standard Spirent WebAvalanche HTTP performance test and Ixia test tools. Testing done with multiple flows through multiple port pairs. Threat Prevention throughput measured with Gateway AV, Anti-Spyware, IPS and Application Control enabled.

<sup>3</sup> VPN throughput measured using UDP traffic at 1280 byte packet size adhering to RFC 2544. All specifications, features and availability are subject to change.

<sup>4</sup> BGP is available only on SonicWall TZ350, TZ400, TZ500 and TZ600.

<sup>5</sup> Pending FIPS and ICSA approval on SOHO 250 and TZ350

<sup>6</sup> All TZ integrated wireless models can support either 2.4GHz or 5GHz band. For dual-band support, please use SonicWall's wireless access point products

## SonicWall TZ series system specifications – TZ400, TZ500 and TZ600

| FIREWALL GENERAL  | TZ400 SERIES   | TZ500 SERIES                | TZ600 SERIES                                      |
|---|--|-----------------------------|---|
| Operating system  | SonicOS  |                             |   |
| Interfaces  | 7x1GbE, 1 USB,<br>1 Console  | 8x1GbE, 2 USB,<br>1 Console | 10x1GbE, 2 USB,<br>1 Console,<br>1 Expansion Slot |
| Power over Ethernet (PoE) support                                   | —  | —                           | TZ600P - 4 ports<br>(4 PoE or 4 PoE+)             |
| Expansion   | USB  | 2 USB                       | Expansion Slot (Rear)*, 2 USB                     |
| Management  | CLI, SSH, Web UI, Capture Security Center, GMS, REST APIs  |                             |   |
| Single Sign-On (SSO) Users  | 500  | 500                         | 500   |
| VLAN interfaces   | 50   | 50                          | 50  |
| Access points supported (maximum)                                   | 16   | 16                          | 24  |
| FIREWALL/VPN PERFORMANCE  | TZ400 SERIES   | TZ500 SERIES                | TZ600 SERIES                                      |
| Firewall inspection throughput <sup>1</sup>                         | 1.3 Gbps   | 1.4 Gbps                    | 1.9 Gbps  |
| Threat Prevention throughput <sup>2</sup>                           | 600 Mbps   | 700 Mbps                    | 800 Mbps  |
| Application inspection throughput <sup>2</sup>                      | 1.2 Gbps   | 1.3 Gbps                    | 1.8 Gbps  |
| IPS throughput <sup>2</sup>   | 900 Mbps   | 1.0 Gbps                    | 1.2 Gbps  |
| Anti-malware inspection throughput <sup>2</sup>                     | 600 Mbps   | 700 Mbps                    | 800 Mbps  |
| TLS/SSL inspection and decryption throughput (DPI SSL) <sup>2</sup> | 180 Mbps   | 225 Mbps                    | 300 Mbps  |
| IPSec VPN throughput <sup>3</sup>                                   | 900 Mbps   | 1.0 Gbps                    | 1.1 Gbps  |
| Connections per second  | 6,000  | 8,000                       | 12,000  |
| Maximum connections (SPI)   | 150,000  | 150,000                     | 150,000   |
| Maximum connections (DPI)   | 125,000  | 125,000                     | 125,000   |
| Maximum connections (DPI SSL)                                       | 25,000   | 25,000                      | 25,000  |
| VPN   | TZ400 SERIES   | TZ500 SERIES                | TZ600 SERIES                                      |
| Site-to-site VPN tunnels  | 20   | 25                          | 50  |
| IPSec VPN clients (maximum)   | 2 (25)   | 2 (25)                      | 2 (25)  |
| SSL VPN licenses (maximum)  | 2 (100)  | 2 (150)                     | 2 (200)   |
| Virtual assist bundled (maximum)                                    | 1 (30-day trial)   | 1 (30-day trial)            | 1 (30-day trial)                                  |
| Encryption/authentication   | DES, 3DES, AES (128, 192, 256-bit)/MD5, SHA-1, Suite B Cryptography  |                             |   |
| Key exchange  | Diffie Hellman Groups 1, 2, 5, 14v   |                             |   |
| Route-based VPN   | RIP, OSPF, BGP   |                             |   |
| VPN features  | Dead Peer Detection, DHCP Over VPN, IPSec NAT Traversal, Redundant VPN Gateway, Route-based VPN  |                             |   |
| Global VPN client platforms supported                               | Microsoft® Windows Vista 32/64-bit, Windows 7 32/64-bit, Windows 8.0 32/64-bit, Windows 8.1 32/64-bit, Windows 10  |                             |   |
| NetExtender   | Microsoft Windows Vista 32/64-bit, Windows 7, Windows 8.0 32/64-bit, Windows 8.1 32/64-bit, Mac OS X 10.4+, Linux FC3+/Ubuntu 7+/OpenSUSE                    |                             |   |
| Mobile Connect  | Apple® iOS, Mac OS X, Google® Android™, Kindle Fire, Chrome, Windows 8.1 (Embedded)  |                             |   |
| SECURITY SERVICES   | TZ400 SERIES   | TZ500 SERIES                | TZ600 SERIES                                      |
| Deep Packet Inspection services                                     | Gateway Anti-Virus, Anti-Spyware, Intrusion Prevention, DPI SSL  |                             |   |
| Content Filtering Service (CFS)                                     | HTTP URL, HTTPS IP, keyword and content scanning, Comprehensive filtering based on file types such as ActiveX, Java, Cookies for privacy, allow/forbid lists |                             |   |
| Comprehensive Anti-Spam Service                                     | Supported  |                             |   |
| Application Visualization   | Yes  | Yes                         | Yes   |
| Application Control   | Yes  | Yes                         | Yes   |
| Capture Advanced Threat Protection                                  | Yes  | Yes                         | Yes   |
| NETWORKING  | TZ400 SERIES   | TZ500 SERIES                | TZ600 SERIES                                      |
| IP address assignment   | Static, (DHCP, PPPoE, L2TP and PPTP client), Internal DHCP server, DHCP relay  |                             |   |
| NAT modes   | 1:1, 1:many, many:1, many:many, flexible NAT (overlapping IPs), PAT, transparent mode  |                             |   |
| Routing protocols <sup>4</sup>                                      | BGP <sup>4</sup> , OSPF, RIPv1/v2, static routes, policy-based routing   |                             |   |
| QoS   | Bandwidth priority, max bandwidth, guaranteed bandwidth, DSCP marking, 802.1e (WMM)  |                             |   |

## SonicWall TZ series system specifications cont'd – TZ400, TZ500 and TZ600

| NETWORKING                                    | TZ400 SERIES   | TZ500 SERIES   | TZ600 SERIES  |
|---|--|--|---|
| Authentication                                | LDAP (multiple domains), XAUTH/RADIUS, SSO, Novell, internal user database, Terminal Services, Citrix, Common Access Card (CAC)            |  |   |
| Local user database                           | 150  |  | 250   |
| VoIP  | Full H.323v1-5, SIP  |  |   |
| Standards                                     | TCP/IP, UDP, ICMP, HTTP, HTTPS, IPSec, ISAKMP/IKE, SNMP, DHCP, PPPoE, L2TP, PPTP, RADIUS, IEEE 802.3                                       |  |   |
| Certifications                                | FIPS 140-2 (with Suite B) Level 2, UC APL, IPv6 (Phase 2), ICSA Network Firewall, ICSA Anti-virus, Common Criteria NDPP (Firewall and IPS) |  |   |
| Common Access Card (CAC)                      |  | Supported  |   |
| High availability                             | Active/standby   | Active/Standby with stateful synchronization   |   |
| HARDWARE                                      | TZ400 SERIES   | TZ500 SERIES   | TZ600 SERIES  |
| Form factor                                   |  | Desktop  |   |
| Power supply                                  | 24W external   | 36W external   | 60W external<br>180W external (TZ600P only)   |
| Maximum power consumption (W)                 | 9.2 / 13.8   | 13.4 / 17.7  | 16.1  |
| Input power                                   | 100-240 VAC, 50-60 Hz, 1 A   |  |   |
| Total heat dissipation                        | 31.3 / 47.1 BTU  | 45.9 / 60.5 BTU  | 55.1 BTU  |
| Dimensions                                    | 3.5 x 13.4 x 19 cm<br>1.38 x 5.28 x 7.48 in  | 3.5 x 15 x 22.5 cm<br>1.38 x 5.91 x 8.86 in  | 3.5 x 18 x 28 cm<br>1.38 x 7.09 x 11.02 in  |
| Weight  | 0.73 kg / 1.61 lbs<br>0.84 kg / 1.85 lbs   | 0.92 kg / 2.03 lbs<br>1.05 kg / 2.31 lbs   | 1.47 kg / 3.24 lbs  |
| WEEE weight                                   | 1.15 kg / 2.53 lbs<br>1.26 kg / 2.78 lbs   | 1.34 kg / 2.95 lbs<br>1.48 kg / 3.26 lbs   | 1.89 kg / 4.16 lbs  |
| Shipping weight                               | 1.37 kg / 3.02 lbs<br>1.48 kg / 3.26 lbs   | 1.93 kg / 4.25 lbs<br>2.07 kg / 4.56 lbs   | 2.48 kg / 5.47 lbs  |
| MTBF (in years)                               | 54.0   | 40.8   | 18.4  |
| Environment (Operating/Storage)               | 32°-105° F (0°-40° C)/-40° to 158° F (-40° to 70° C)   |  |   |
| Humidity                                      | 5-95% non-condensing   |  |   |
| REGULATORY                                    | TZ400 SERIES   | TZ500 SERIES   | TZ600 SERIES  |
| Major regulatory compliance (wired models)    | FCC Class B, ICES Class B, CE (EMC, LVD, RoHS), C-Tick, VCCI Class B, UL, cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH, KCC/MSIP, ANATEL | FCC Class B, ICES Class B, CE (EMC, LVD, RoHS), C-Tick, VCCI Class B, UL, cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH, BSMI, KCC/MSIP, ANATEL | FCC Class A, ICES Class A, CE (EMC, LVD, RoHS), C-Tick, VCCI Class A, UL cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH, KCC/MSIP, ANATEL |
| Major regulatory compliance (wireless models) | FCC Class B, FCC RF ICES Class B, IC RF CE (RED, RoHS), RCM, VCCI Class B, MIC/TELEC, UL, cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH   | FCC Class B, FCC RF ICES Class B, IC RF CE (RED, RoHS), RCM, VCCI Class B, MIC/TELEC, UL, cUL, TUV/GS, CB, Mexico CoC by UL, WEEE, REACH         | —   |

## SonicWall TZ series system specifications cont'd – TZ400, TZ500 and TZ600

| INTEGRATED WIRELESS            | TZ400 SERIES   | TZ500 SERIES | TZ600 SERIES |
|--------------------------------|--|--------------|--------------|
| Standards                      | 802.11a/b/g/n/ac (WEP, WPA, WPA2, 802.11i, TKIP, PSK, 02.1x, EAP-PEAP, EAP-TTLS)   |              | —            |
| Frequency bands <sup>5</sup>   | 802.11a: 5.180-5.825 GHz; 802.11b/g: 2.412-2.472 GHz; 802.11n: 2.412-2.472 GHz, 5.180-5.825 GHz; 802.11ac: 5.180-5.825 GHz   |              | —            |
| Operating Channels             | 802.11a: US and Canada 12, Europe 11, Japan 4, Singapore 4, Taiwan 4; 802.11b/g: US and Canada 1-11, Europe 1-13, Japan (14-802.11b only); 802.11n (2.4 GHz): US and Canada 1-11, Europe 1-13, Japan 1-13; 802.11n (5 GHz): US and Canada 36-48/149-165, Europe 36-48, Japan 36-48, Spain 36-48/52-64; 802.11ac: US and Canada 36-48/149-165, Europe 36-48, Japan 36-48, Spain 36-48/52-64   |              | —            |
| Transmit output power          | Based on the regulatory domain specified by the system administrator   |              | —            |
| Transmit power control         | Supported  |              | —            |
| Data rates supported           | 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps per channel; 802.11b: 1, 2, 5.5, 11 Mbps per channel; 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps per channel; 802.11n: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2, 15, 30, 45, 60, 90, 120, 135, 150 Mbps per channel; 802.11ac: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2, 86.7, 96.3, 15, 30, 45, 60, 90, 120, 135, 150, 180, 200, 32.5, 65, 97.5, 130, 195, 260, 292.5, 325, 390, 433.3, 65, 130, 195, 260, 390, 520, 585, 650, 780, 866.7 Mbps per channel |              | —            |
| Modulation technology spectrum | 802.11a: Orthogonal Frequency Division Multiplexing (OFDM); 802.11b: Direct Sequence Spread Spectrum (DSSS); 802.11g: Orthogonal Frequency Division Multiplexing (OFDM)/Direct Sequence Spread Spectrum (DSSS); 802.11n: Orthogonal Frequency Division Multiplexing (OFDM); 802.11ac: Orthogonal Frequency Division Multiplexing (OFDM)  |              | —            |

## SonicWall TZ series specifications – TZ570 and TZ670

| FIREWALL GENERAL   | TZ570 SERIES  | TZ670 SERIES  |
|--|---|---|
| Operating system   | SonicOS 7.0   |   |
| Interfaces   | 8x1GbE, 2x5GbE, 2 USB 3.0,<br>1 Console   | 8x1GbE, 2x10GbE, 2 USB 3.0,<br>1 Console                |
| Power over Ethernet (PoE) support                                      | TZ570P (5 PoE or 3PoE+)   | —   |
| Expansion  | Storage Expansion Slot (Up to 256GB)  | Storage Expansion Slot (Up to 256GB)<br>(32GB included) |
| Management   | Network Security Manager, CLI, SSH, Web UI, GMS, REST APIs  |   |
| Single Sign-On (SSO) Users   | 2,500   | 2,500   |
| VLAN interfaces  | 256   | 256   |
| Access points supported (maximum)                                      | 32  | 32  |
| FIREWALL/VPN PERFORMANCE   | TZ570 SERIES  | TZ670 SERIES  |
| Firewall inspection throughput <sup>1</sup>                            | 4.00 Gbps   | 5.00 Gbps   |
| Threat Prevention throughput <sup>2</sup>                              | 2.00 Gbps   | 2.50 Gbps   |
| Application inspection throughput <sup>2</sup>                         | 2.5 Gbps  | 3.0 Gbps  |
| IPS throughput <sup>2</sup>  | 2.5 Gbps  | 3.0 Gbps  |
| Anti-malware inspection throughput <sup>2</sup>                        | 2.00 Gbps   | 2.50 Gbps   |
| TLS/SSL inspection and decryption throughput<br>(DPI SSL) <sup>2</sup> | 750 Mbps  | 800 Mbps  |
| IPSec VPN throughput <sup>3</sup>                                      | 1.80 Gbps   | 2.10 Gbps   |
| Connections per second   | 16,000  | 25,000  |
| Maximum connections (SPI)  | 1,250,000   | 1,500,000   |
| Maximum connections (DPI)  | 400,000   | 500,000   |
| Maximum connections (DPI SSL)  | 30,000  | 30,000  |
| VPN  | TZ570 SERIES  | TZ670 SERIES  |
| Site-to-site VPN tunnels   | 200   | 250   |
| IPSec VPN clients (maximum)  | 10 (500)  | 10 (500)  |
| SSL VPN licenses (maximum)   | 2 (200)   | 2 (250)   |
| Encryption/authentication  | DES, 3DES, AES (128, 192, 256-bit)/MD5, SHA-1, Suite B Cryptography   |   |
| Key exchange   | Diffie Hellman Groups 1, 2, 5, 14v  |   |
| Route-based VPN  | RIP, OSPF, BGP  |   |
| VPN features   | Dead Peer Detection, DHCP Over VPN, IPSec NAT Traversal,<br>Redundant VPN Gateway, Route-based VPN  |   |
| Global VPN client platforms supported                                  | Microsoft® Windows 10   |   |
| NetExtender  | Microsoft® Windows 10, Linux  |   |
| Mobile Connect   | Apple® iOS, Mac OS X, Google® Android™, Kindle Fire, Chrome OS, Windows 10  |   |
| SECURITY SERVICES  | TZ570 SERIES  | TZ670 SERIES  |
| Deep Packet Inspection services  | Gateway Anti-Virus, Anti-Spyware, Intrusion Prevention, DPI SSL   |   |
| Content Filtering Service (CFS)  | HTTP URL, HTTPS IP, keyword and content scanning, Comprehensive filtering based on file types<br>such as ActiveX, Java, Cookies for privacy, allow/forbid lists |   |
| Comprehensive Anti-Spam Service  | Yes   |   |
| Application Visualization  | Yes   |   |
| Application Control  | Yes   |   |
| Capture Advanced Threat Protection                                     | Yes   |   |
| DNS Security   | Yes   |   |



## SonicWall TZ series specifications cont'd – TZ570 and TZ670

| NETWORKING  | TZ570 SERIES  | TZ670 SERIES   |
|---|---|--|
| IP address assignment                                     | Static, (DHCP, PPPoE, L2TP and PPTP client), Internal DHCP server, DHCP relay   |  |
| NAT modes   | 1:1, 1:many, many:1, many:many, flexible NAT (overlapping IPs), PAT, transparent mode   |  |
| Routing protocols   | BGP, OSPF, RIPv1/v2, static routes, policy-based routing  |  |
| QoS   | Bandwidth priority, max bandwidth, guaranteed bandwidth, DSCP marking, 802.1e (WMM)   |  |
| Authentication  | LDAP (multiple domains), XAUTH/RADIUS, SSO, Novell, internal user database, Terminal Services, Citrix, Common Access Card (CAC)   |  |
| Local user database                                       | 250   |  |
| VoIP  | Full H.323v1-5, SIP   |  |
| Standards   | TCP/IP, UDP, ICMP, HTTP, HTTPS, IPSec, ISAKMP/IKE, SNMP, DHCP, PPPoE, L2TP, PPTP, RADIUS, IEEE a802.3   |  |
| Certifications pending                                    | FIPS 140-2 (with Suite B) Level 2, IPv6 (Phase 2), ICSA Network Firewall, ICSA Anti-virus, Common Criteria NDPP (Firewall and IPS)  |  |
| HARDWARE  | TZ570 SERIES  | TZ670 SERIES   |
| Form Factor   | Desktop <sup>5</sup>  |  |
| Power supply  | 60W external<br>180W external<br>(TZ570P only)  | 60W external   |
| Maximum power consumption (W)                             | 13.1  | 13.1   |
| Input Voltage & Frequency                                 | 100-240 VAC, 50-60 Hz   | 100-240 VAC, 50-60 Hz  |
| Total heat dissipation                                    | 45.9 / 60.5 BTU   | 55.1 BTU   |
| Dimensions  | 3.5 x 15 x 22.5 (cm)<br>1.38 x 5.91 x 8.85 in   | 3.5 x 15 x 22.5 (cm)<br>1.38 x 5.91 x 8.85 in  |
| Weight  | 0.97 kg / 2.14 lbs  | 0.97 kg / 2.14 lbs   |
| WEEE weight   | 1.42 kg / 3.13 lbs  | 1.42 kg / 3.13 lbs   |
| Shipping weight   | 1.93 kg / 4.25 lbs  | 1.93 kg / 4.25 lbs   |
| MTBF @25°C in years                                       | 26.1  | 43.9   |
| Environment (Operating/Storage)                           | 32°-105° F (0°-40° C)/-40° to 158° F (-40° to 70° C)  |  |
| Humidity  | 5-95% non-condensing  |  |
| REGULATORY  | TZ570 SERIES  | TZ670 SERIES   |
| Major regulatory compliance (wired models - TZ670, TZ570) | FCC Class B, FCC , ICES Class B, CE (EMC, LVD, RoHS), C-Tick, VCCI Class B, UL/cUL, TUV/GS, CB, Mexico DGN notice by UL, WEEE, REACH, BSMI, KCC/MSIP, ANATEL  | FCC Class B, FCC , ICES Class B, CE (EMC, LVD, RoHS), C-Tick, VCCI Class B, UL/cUL, TUV/GS, CB, Mexico DGN notice by UL, WEEE, REACH, BSMI, KCC/MSIP, ANATEL |
| Major regulatory compliance (wireless models - TZ570W)    | FCC Class B, FCC P15C, FCC P15E, ICES Class B, ISED/IC, CE (RED, RoHS), C-Tick, VCCI Class B, Japan Wireless, UL/cUL, TUV/GS, CB, Mexico DGN notice by UL, WEEE, REACH, BSMI, NCC (TW) KCC/MSIP, SRRC, ANATEL | —  |
| Major regulatory compliance (PoE models - TZ570P)         | FCC Class A, ICES Class A, CE (EMC, LVD, RoHS), C-Tick, VCCI Class A, UL/cUL, TUV/GS, CB, Mexico DGN notice by UL, WEEE, REACH, BSMI, KCC/MSIP, ANATEL  | —  |

## SonicWall TZ series specifications cont'd – TZ570 and TZ670

| INTEGRATED WIRELESS            | TZ570 SERIES   | TZ670 SERIES |
|--------------------------------|--|--------------|
| Standards                      | 802.11a/b/g/n/ac (WEP, WPA, WPA2, 802.11i, TKIP, PSK, 02.1x, EAP-PEAP, EAP-TTLS)   | —            |
| Frequency bands <sup>5</sup>   | 802.11a: 5.180-5.825 GHz; 802.11b/g: 2.412-2.472 GHz; 802.11n: 2.412-2.472 GHz, 5.180-5.825 GHz; 802.11ac: 5.180-5.825 GHz   | —            |
| Operating Channels             | 802.11a: US and Canada 12, Europe 11, Japan 4, Singapore 4, Taiwan 4; 802.11b/g: US and Canada 1-11, Europe 1-13, Japan (14-802.11b only); 802.11n (2.4 GHz): US and Canada 1-11, Europe 1-13, Japan 1-13; 802.11n (5 GHz): US and Canada 36-48/149-165, Europe 36-48, Japan 36-48, Spain 36-48/52-64; 802.11ac: US and Canada 36-48/149-165, Europe 36-48, Japan 36-48, Spain 36-48/52-64   | —            |
| Transmit output power          | Based on the regulatory domain specified by the system administrator   | —            |
| Transmit power control         | Supported  | —            |
| Data rates supported           | 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps per channel; 802.11b: 1, 2, 5.5, 11 Mbps per channel; 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps per channel; 802.11n: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2, 15, 30, 45, 60, 90, 120, 135, 150 Mbps per channel; 802.11ac: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2, 86.7, 96.3, 15, 30, 45, 60, 90, 120, 135, 150, 180, 200, 32.5, 65, 97.5, 130, 195, 260, 292.5, 325, 390, 433.3, 65, 130, 195, 260, 390, 520, 585, 650, 780, 866.7 Mbps per channel | —            |
| Modulation technology spectrum | 802.11a: Orthogonal Frequency Division Multiplexing (OFDM); 802.11b: Direct Sequence Spread Spectrum (DSSS); 802.11g: Orthogonal Frequency Division Multiplexing (OFDM)/Direct Sequence Spread Spectrum (DSSS); 802.11n: Orthogonal Frequency Division Multiplexing (OFDM); 802.11ac: Orthogonal Frequency Division Multiplexing (OFDM)  | —            |

<sup>1</sup>Testing Methodologies: Maximum performance based on RFC 2544 (for firewall). Actual performance may vary depending on network conditions and activated services.

<sup>2</sup>Threat Prevention/GatewayAV/Anti-Spyware/IPS throughput measured using industry standard Spirent WebAvalanche HTTP performance test and Ixia test tools. Testing done with multiple flows through multiple port pairs. Threat Prevention throughput measured with Gateway AV, Anti-Spyware, IPS and Application Control enabled.

<sup>3</sup>VPN throughput measured using UDP traffic at 1280 byte packet size adhering to RFC 2544. All specifications, features and availability are subject to change.

<sup>4</sup>For rack mount, separate rack mount kit available.

<sup>5</sup>All TZ integrated wireless models can support either 2.4GHz or 5GHz band. For dual-band support, please use SonicWall's wireless access point products.

## SonicWall TZ Series ordering information

| Product   | SKU         |
|---|-------------|
| SOHO 250 with 1-year TotalSecure Advanced Edition                   | 02-SSC-1815 |
| SOHO 250 Wireless-AC with 1-year TotalSecure Advanced Edition       | 02-SSC-1824 |
| TZ300 with 1-year TotalSecure Advanced Edition                      | 01-SSC-1702 |
| TZ300 Wireless-AC with 1-year TotalSecure Advanced Edition          | 01-SSC-1703 |
| TZ300P with 1-year TotalSecure Advanced Edition                     | 02-SSC-0602 |
| TZ350 with 1-year TotalSecure Advanced Edition                      | 02-SSC-1843 |
| TZ350 Wireless-AC with 1-year TotalSecure Advanced Edition          | 02-SSC-1851 |
| TZ400 with 1-year TotalSecure Advanced Edition                      | 01-SSC-1705 |
| TZ400 Wireless-AC with 1-year TotalSecure Advanced Edition          | 01-SSC-1706 |
| TZ500 with 1-year TotalSecure Advanced Edition                      | 01-SSC-1708 |
| TZ500 Wireless-AC with 1-year TotalSecure Advanced Edition          | 01-SSC-1709 |
| TZ570 with 1-year TotalSecure Essential Edition                     | 02-SSC-5651 |
| TZ570W with 1-year TotalSecure Essential Edition                    | 02-SSC-5649 |
| TZ570P with 1-year TotalSecure Essential Edition                    | 02-SSC-5653 |
| TZ600 with 1-year TotalSecure Advanced Edition                      | 01-SSC-1711 |
| TZ600P with 1-year TotalSecure Advanced Edition                     | 02-SSC-0600 |
| TZ670 with 1-year TotalSecure Essential Edition                     | 02-SSC-5640 |
| <b>High availability options (each unit must be the same model)</b> |             |
| TZ500 High Availability   | 01-SSC-0439 |
| TZ570 High Availability   | 02-SSC-5694 |
| TZ570P High Availability  | 02-SSC-5655 |
| TZ600 High Availability   | 01-SSC-0220 |
| TZ670 High Availability   | 02-SSC-5654 |

| Services  | SKU         |
|---|-------------|
| <b>For SonicWall SOHO 250 Series</b>  |             |
| Advanced Gateway Security Suite - Capture ATP, Threat Prevention, and 24x7 Support (1-year) | 02-SSC-1726 |
| Capture Advanced Threat Protection for SOHO 250 (1-year)                                    | 02-SSC-1732 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)                   | 02-SSC-1750 |
| Content Filtering Service (1-year)  | 02-SSC-1744 |
| Comprehensive Anti-Spam Service (1-year)  | 02-SSC-1823 |
| 24x7 Support (1-year)   | 02-SSC-1720 |
| <b>For SonicWall TZ300 Series</b>   |             |
| Advanced Gateway Security Suite - Capture ATP, Threat Prevention, and 24x7 Support (1-year) | 01-SSC-1430 |
| Capture Advanced Threat Protection for TZ300 (1-year)                                       | 01-SSC-1435 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)                   | 01-SSC-0602 |
| Content Filtering Service (1-year)  | 01-SSC-0608 |
| Comprehensive Anti-Spam Service (1-year)  | 01-SSC-0632 |
| 24x7 Support (1-year)   | 01-SSC-0620 |
| <b>For SonicWall TZ350 Series</b>   |             |
| Advanced Gateway Security Suite - Capture ATP, Threat Prevention, and 24x7 Support (1-year) | 02-SSC-1773 |
| Capture Advanced Threat Protection for TZ350 (1-year)                                       | 02-SSC-1779 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)                   | 02-SSC-1797 |
| Content Filtering Service (1-year)  | 02-SSC-1791 |
| Comprehensive Anti-Spam Service (1-year)  | 02-SSC-1809 |
| 24x7 Support (1-year)   | 02-SSC-1767 |

## SonicWall TZ Series ordering information

|   |             |
|---|-------------|
| <b>For SonicWall TZ400 Series</b>   |             |
| Advanced Gateway Security Suite - Capture ATP, Threat Prevention, and 24x7 Support (1-year)                                 | 01-SSC-1440 |
| Capture Advanced Threat Protection for TZ400 (1-year)   | 01-SSC-1445 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)   | 01-SSC-0534 |
| Content Filtering Service (1-year)  | 01-SSC-0540 |
| Comprehensive Anti-Spam Service (1-year)  | 01-SSC-0561 |
| 24x7 Support (1-year)   | 01-SSC-0552 |
| <b>For SonicWall TZ500 Series</b>   |             |
| Advanced Gateway Security Suite - Capture ATP, Threat Prevention, and 24x7 Support (1-year)                                 | 01-SSC-1450 |
| Capture Advanced Threat Protection for TZ500 (1-year)   | 01-SSC-1455 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)   | 01-SSC-0458 |
| Content Filtering Service (1-year)  | 01-SSC-0464 |
| Comprehensive Anti-Spam Service (1-year)  | 01-SSC-0482 |
| 24x7 Support (1-year)   | 01-SSC-0476 |
| <b>For SonicWall TZ600 Series</b>   |             |
| Advanced Gateway Security Suite - Capture ATP, Threat Prevention, and 24x7 Support (1-year)                                 | 01-SSC-1460 |
| Capture Advanced Threat Protection for TZ600 (1-year)   | 01-SSC-1465 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)   | 01-SSC-0228 |
| Content Filtering Service (1-year)  | 01-SSC-0234 |
| Comprehensive Anti-Spam Service (1-year)  | 01-SSC-0252 |
| 24x7 Support (1-year)   | 01-SSC-0246 |
| <b>For SonicWall TZ670 Series</b>   |             |
| Essential Protection Service Suite - Capture ATP, Threat Prevention, Content Filtering, Anti-Spam and 24x7 Support (1-year) | 02-SSC-5053 |
| Capture Advanced Threat Protection for TZ670 (1-year)   | 02-SSC-5035 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)   | 02-SSC-5059 |
| Content Filtering Service (1-year)  | 02-SSC-5047 |
| Comprehensive Anti-Spam Service (1-year)  | 02-SSC-5041 |
| 24x7 Support (1-year)   | 02-SSC-5029 |
| <b>For SonicWall TZ570 Series (TZ570)</b>   |             |
| Essential Protection Service Suite - Capture ATP, Threat Prevention, Content Filtering, Anti-Spam and 24x7 Support (1-year) | 02-SSC-5137 |
| Capture Advanced Threat Protection for TZ570 (1-year)   | 02-SSC-5083 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)   | 02-SSC-5155 |
| Content Filtering Service (1-year)  | 02-SSC-5119 |
| Comprehensive Anti-Spam Service (1-year)  | 02-SSC-5101 |
| 24x7 Support (1-year)   | 02-SSC-5065 |
| <b>For SonicWall TZ570 Series (TZ570W)</b>  |             |
| Essential Protection Service Suite - Capture ATP, Threat Prevention, Content Filtering, Anti-Spam and 24x7 Support (1-year) | 02-SSC-5149 |
| Capture Advanced Threat Protection for TZ570W (1-year)  | 02-SSC-5095 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)   | 02-SSC-5167 |
| Content Filtering Service (1-year)  | 02-SSC-5131 |
| Comprehensive Anti-Spam Service (1-year)  | 02-SSC-5113 |
| 24x7 Support (1-year)   | 02-SSC-5077 |
| <b>For SonicWall TZ570 Series (TZ570P)</b>  |             |
| Essential Protection Service Suite - Capture ATP, Threat Prevention, Content Filtering, Anti-Spam and 24x7 Support (1-year) | 02-SSC-5143 |
| Capture Advanced Threat Protection for TZ570P (1-year)  | 02-SSC-5089 |
| Gateway Anti-Virus, Intrusion Prevention and Application Control (1-year)   | 02-SSC-5161 |
| Content Filtering Service (1-year)  | 02-SSC-5125 |
| Comprehensive Anti-Spam Service (1-year)  | 02-SSC-5107 |
| 24x7 Support (1-year)   | 02-SSC-5071 |

## Accessories

## SKU

### TZ670/570 Series

|  |             |
|--|-------------|
| SonicWall TZ670/570 Series FRU Power Supply            | 02-SSC-3078 |
| SonicWall TZ670/570 Series Rack Mount Kit              | 02-SSC-3112 |
| SonicWall 32GB Storage Module for TZ670/570 Series     | 02-SSC-3114 |
| SonicWall 64GB Storage Module for TZ670/570 Series     | 02-SSC-3115 |
| SonicWall 128GB Storage Module for TZ670/570 Series    | 02-SSC-3116 |
| SonicWall 256GB Storage Module for TZ670/570 Series    | 02-SSC-3117 |
| SonicWall Micro USB Console Cable for TZ670/570 Series | 02-SSC-5173 |

### TZ600/500/400/350/300, SOHO 250 Series

|   |             |
|---|-------------|
| SonicWall TZ600 Rack Mount Kit  | 01-SSC-0225 |
| SonicWall TZ600 Series FRU Power Supply                               | 01-SSC-0280 |
| SonicWall TZ500 Series Rack Mount Kit                                 | 01-SSC-0438 |
| SonicWall TZ500 Series FRU Power Supply                               | 01-SSC-0437 |
| SonicWall TZ400 Series Rack Mount Kit                                 | 01-SSC-0525 |
| SonicWall TZ350, TZ300 Series Rack Mount Kit                          | 01-SSC-0742 |
| SonicWall TZ400, TZ350, TZ300, SOHO 250, SOHO Series FRU Power Supply | 01-SSC-0709 |
| SonicWall TZ300 PoE FRU Power Supply                                  | 02-SSC-0613 |

### SonicWall SFP/SFP+ Modules

|   |             |
|---|-------------|
| 10GB-SR SFP+ Short Reach Fiber Module Multi-Mode No Cable | 01-SSC-9785 |
| 10GB-LR SFP+ Long Reach Fiber Module Single-Mode No Cable | 01-SSC-9786 |
| 10GB SFP+ Copper with 1M Twinax Cable                     | 01-SSC-9787 |
| 10GB SFP+ Copper with 3M Twinax Cable                     | 01-SSC-9788 |
| 1GB-SX SFP Short Haul Fiber Module Multi-Mode No Cable    | 01-SSC-9789 |
| 1GB-LX SFP Long Haul Fiber Module Single-Mode No Cable    | 01-SSC-9790 |
| 1GB-RJ45 SFP Copper Module No Cable                       | 01-SSC-9791 |
| SonicWall SFP+ 10GBASE-T Transceiver Copper RJ45 Module   | 02-SSC-1874 |

## Regulatory model numbers

|                             |                               |
|-----------------------------|-------------------------------|
| SOHO/SOHO Wireless          | APL31-0B9/APL41-0BA           |
| SOHO 250/SOHO 250 Wireless  | APL41-0D6/APL41-0BA           |
| TZ300/TZ300 Wireless/TZ300P | APL28-0B4/APL28-0B5/APL47-0D2 |
| TZ350/TZ350 Wireless        | APL28-0B4/APL28-0B5           |
| TZ400/TZ400 Wireless        | APL28-0B4/APL28-0B5           |
| TZ500/TZ500 Wireless        | APL29-0B6/APL29-0B7           |
| TZ600/TZ600P                | APL30-0B8/APL48-0D3           |
| TZ670                       | APL62-0F7                     |
| TZ570/ TZ570W/ TZ570P       | APL62-0F7/APL62-0F8/APL63-0F9 |

## About SonicWall

SonicWall delivers Boundless Cybersecurity for the hyper-distributed era and a work reality where everyone is remote, mobile and unsecure. By knowing the unknown, providing real-time visibility and enabling breakthrough economics, SonicWall closes the cybersecurity business gap for enterprises, governments and SMBs worldwide. For more information, visit [www.sonicwall.com](http://www.sonicwall.com).

The Gartner Peer Insights Customers' Choice logo is a trademark and service mark of Gartner, Inc., and/or its affiliates, and is used herein with permission. All rights reserved. Gartner Peer Insights Customers' Choice distinctions are determined by the subjective opinions of individual end-user customers based on their own experiences, the number of published reviews on Gartner Peer Insights and overall ratings for a given vendor in the market, as further described here, and are not intended in any way to represent the views of Gartner or its affiliates.